

SD-250A

1/3" Indoor Dome Camera



Features

- Excellent picture quality and color reproduction
- Suitable for any commercial or residential application
- Available in various kind of board lenses



Specifications :

Model No.		SD-250A
Pickup Device		Color 1/3" SHARP CCD
Pickup Elements	NTSC	510 (H) X 492 (V)
	PAL	512 (H) X 582 (V)
Scanning System	NTSC	2:1 Interlace; V: 60Hz, H: 15,750KHz
	PAL	2:1 Interlace; V: 50Hz, H: 15,625KHz
Sync. System		Internal sync.
Video Output		1Vp-p Composite Output, 75 ohms
Lens		Standard: f=3.6mm, Options: f=4.3mm, f=6.0mm
Resolution		420TV Lines (Horizontal)
Gamma Correction		0.45
Minimum illumination		0.3 Lux / F=2.0
S/N Ratio		48dB, AGC off
Shutter Control	NTSC	Auto: 1/60 to 1/100,000 Sec.
	PAL	Auto: 1/50 to 1/100,000 Sec.
White Balance		Auto
Gain Control		Auto
Power Consumption		90 mA (MAX.)
Ambient		-10°C~+50 °C (14 °F~122 °F)
Power Source		DC 12V ±10%
Dimension		96(φ) X 68 (L) mm
Weight		Approx. 150g

Design and specifications are subject to change without prior notice.