

SID-252

1/3" Indoor IR Dome Camera



Features

- Day / Night Camera with real 0 lux performance
- Free from focus shifting under IR lighting
- Built-in 24 IR LEDs, up to 15 meters (49 feet) IR view distance
- 3 Axis designed for easy horizontal or vertical view adjustment



Specifications :

Model No.		SID-252
Pickup Device		Color 1/3" SHARP CCD
Pickup Elements	NTSC	510 (H) X 492 (V)
	PAL	512 (H) X 582 (V)
Scanning System	NTSC	2:1 Interlace; V: 60Hz, H: 15,750KHz
	PAL	2:1 Interlace; V: 50Hz, H: 15,625KHz
Sync. System		Internal sync.
Video Output		1Vp-p Composite Output, 75 ohms
Lens		Standard: f=3.6mm, Options: f=4.3mm, f=6.0mm
Resolution		420TV Lines (Horizontal)
Gamma Correction		0.45
Minimum Illumination		0.3 Lux @ F=2.0; 0 Lux when IR LED ON
S/N Ratio		> 48dB, AGC off
Shutter Control	NTSC	Auto: 1/60 to 1/100,000 Sec.
	PAL	Auto: 1/50 to 1/100,000 Sec.
White Balance		Auto
Gain Control		Auto
IR LED Power		CDS Auto Control
IR Wavelength		850 nm
IR LED Range		15M
IR LED		24IR-LED / Life: 6000 Hours
Power Source		DC 12V ± 10%
Power Consumption	IR ON	350mA
	IR OFF	90mA
Operation Temperature		-10° C ~ +50° C (14° F ~ 122° F)
Dimension		93 (φ) X 80 (L) mm
Weight		Approx. 170 g

Design and specifications are subject to change without prior notice.