

SW-652

1/3" Weatherproof IR Color Camera



Features

- 1/3" SONY SUPER HAD II CCD
- SONY EFFIO DSP achieves 650TVL high resolution quality
- Digital Noise Reduction (DNR) for better low lux performance
- Day/Night Camera with real 0 lux performance
- Built-in 24 IR LED up to 15 meter (49 feet) IR view distance
- Weatherproof class IP 67



Specifications :

Model No.	SW-652	
Pickup Device	Color 1/3" SONY Super HAD II CCD	
Pickup Elements	NTSC	976 (H) X 494 (V)
	PAL	976 (H) X 582 (V)
Scanning System	NTSC	2:1 Interlace; V: 60Hz, H: 15.750KHz
	PAL	2:1 Interlace; V: 50Hz, H: 15.625KHz
Sync. System	Internal sync	
Video Output	1Vp-p Composite Output, 75 ohms	
Lens	Board lens f=4.3mm, 6.0mm	
Resolution	650TV Lines (Horizontal)	
Gamma Correction	0.45	
Minimum Illumination	0.1 Lux @ F1.2 / 0 Lux @ F1.2	
S/N Ratio	> 50dB, AGC off	
Shutter Control	NTSC	Auto: 1/60 to 1/100,000 Sec.
	PAL	Auto: 1/50 to 1/100,000 Sec.
White Balance	Auto	
Gain Control	Auto	
IR LED Power	Photo Sensor Auto Control	
IR Wavelength	850nm	
IR LED Range	15M(49 feet)	
IR LED	24IR-LED / Life: 8000 Hours	
Power Source	DC 12V ±10%	
Power Consumption	IR ON	380mA
	IR OFF	90mA
Operation Temperature	-10°C~+50°C (14°F~122°F)	
Dimension	82 (L) X 56.5 (φ) mm w/o bracket	
Weight	Approx. 480 g w/o bracket	

Design and specifications are subject to change without prior notice.