

# SIV-540E

1/3" Indoor Vandal - Proof Dome Camera



## Features

- 1/3" Color SONY Super HAD CCD Sensor
- High resolution 540 TV Lines providing fine, crisp and vivid high resolution image
- Built-in Aspherical vari-focal auto IRIS lens f=3.7~12mm apply for different angles of view (Available in varies board lenses)
- Internal 3 Axis mechanical designed for easy horizontal or vertical view adjustment
- Compact design and super tough vandal resist dome



1/3"CCD



540TVL



Vandal Proof



Auto IRIS



Easy Installed



0.1 Low Lux

## Specifications :

Model No.	SIV-540E	
Pickup Device	Color 1/3" SONY Super HAD CCD	
Pickup Elements	NTSC	811 (H) X 508 (V)
	PAL	795 (H) X 596 (V)
Scanning System	NTSC	2:1 Interlace, V:60Hz, H:15,750KHz
	PAL	2:1 Interlace, V:50Hz, H:15,625KHz
Sync.	Internal Sync.	
Video Output	1Vp-p Composite, 75 ohms	
Lens	Aspherical Vari-Focal Auto IRIS f=3.7~12mm / F1.4~3.6	
	Optional board lenses f=3.6, 4.3, 6.0, 8.0mm / F2.0	
Resolution	540 TV Lines (Horizontal)	
Gamma Correction	0.45	
Minimum Illumination	0.1 Lux @ F1.4 (30 IRE, AGC ON)	
S/N Ratio	> 50 dB, AGC off	
Shutter Control	NTSC	Auto, 1/60 to 1/100,000 sec.
	PAL	Auto, 1/50 to 1/100,000 sec.
White Balance	Auto	
Gain Control	Auto	
Power Source	DC12V±10%	
Power Consumption	Max.1.5W	
Operation Temperature	-10° C ~ +50° C / 14° F ~ 122° F	
Operation Humidity	RH85% or less	
Dimension	85 (H) x 143 (φ)	
Weight	350 g	

Design and specifications are subject to change without prior notice.